

Power, performance, robustness



www.france-etuves.com

XL RANGE

INDUSTRIAL OVENS

INDUSTRIAL OVENS XL up to 200°C

XL ovens are suitable for processes requiring a powerful airflow and air change. For all intensive drying applications, heating, polymerization, ... or any other thermal test.

A robust construction.

External sheets made of steel. White and blue epoxy paints.
 Inner casing made of stainless steel corrosion-resistant.
 Simplified calibration with the Ø 20mm access port on the left side.
 Thick insulation asbestos free : excellent thermal stability, low heat loss, energy cost reduced, low surface temperatures.

A powerful vertical airflow for an amazing temperature homogeneity !

An exclusive ventilation system : air is sucked in the upper part of the oven. Then, it is heated and blown from the bottom back part

A wonderful adjustable air change.

Large inlet and outlet air. The various clearances are removed effectively.
 Adjustable exhaust air flap. The output is connectable to an extraction system.

A surprising heating power.

A rapid rise in temperature.

Work safely.

Independent thermostat and adjustable safety controller with digital display (classes 2 and 3.1). Heating is cut off in case of failure, overload or over-temperature.
 Visual and audible alarms.



Loading shelves

2 shelves provided with anti-tilting guide bars. Multiple levels of loading.



An accurate and efficient temperature control.

C3000 PID electronic controller. Easy to use. Precision : 0.1°C. Measurement by PT100 probe.
 Functions : delayed start, heating-up ramp, en cycle timer, repeat loop.



XL0112


XL0343

XL0490

XL0686

XL0980

OPTIONS




2 Door with viewing window



3 Fan speed controller



4 Air outlet extractor



5 Air cooling extractor



6 Digital weekly program timer



7 Cycles profiler 4 prog 16 seg



8 Profiler+digital recorder 3 channels



9 Inside lighting




10 Stop fan and heating



11 Access port Ø 60mm



12 Factory calibration 1 point




13 Homogeneity control 9/15 points

ACCESSORIES



1 Shelf with guide bars



2 Recovery tray



3 Fixed subframe



4 Subframe with casters



5 Paperless recorder 2 channels



6 Portable paperless recorder with graphical screen 4 or 6 channels



XL1000

XL1400

XL1800

- 1 Temperature extension max. 300°C**
- 2 Door with viewing window**
To see inside of the oven.
- 3 Fan speed controller**
Adjusts the speed of the air fan.
- 4 Air outlet extractor**
Evacuates the exhaust air into a duct system.
- 5 Air cooling extractor**
Enables cooling the temperature in the volume. Started by switch.
- 6 Digital weekly program timer**
Set times of operation of the oven for each day of the week. Ventilation is stopped only when the oven temperature has fallen to 80°C to prevent damage to the fans.
- 7 Cycles profiler 4 programs with 16 segments each**
Ideal if you need to heat at different temperatures during your process or provide gentle temperature drops.
- 8 Profiler + digital recorder 3 channels**
Allows the creation of temperature programs and to record those measured. With USB and RJ45 plugs.
- 9 Inside lighting**
With switch on the control panel.
- 10 Stop fan and heating when the door is opened**
- 11 Access port Ø60mm.**
Centered on the left side. Allows the passage of cables or sensors.
- 12 Factory calibration certificate**
1 temperature (105°C, 150°C or 200°C). Measurement in the center of the working chamber (according to FD X 15-140).
- 13 homogeneity control certificate**
1 temperature (105°C, 150°C or 200°C). Measurement at 9 points in the working chamber (according to FD X 15-140).
- 1 Loading shelf with 2 guide bars**
Chromed steel. Max. loading : 30kg.
Or reinforced shelf : max. loading 60kg.
Anti-tilting guide bars.
- 2 Recovery tray**
Stainless steel, height : 20mm. Protects the floor of the oven.
- 3 Fixed subframe or subframe with casters**
(Except XL1400 et XL1800). Elevates the oven for a more comfortable loading. Casters with brakes.
- 5 Paperless recorder 2 channels**
Saves the temperatures measured by two mobile sensors.

Data acquisition software for recorder 2 channels
Can retrieve stored data.
- 6 Portable paperless recorder with graphical screen 4 or 6 channels**
Large graphical display for real monitoring of temperature changes. With USB and RJ45 plugs, and 4 or 6 connectors for mobile sensors.
- 7 Thermocouple J length 3m with plug**
Accessory for recorders.

TECHNICAL DATA

	XL0112	XL0343	XL0490	XL0686	XL0980	XL1000	XL1400	XL1800
Working volume (L)	112	343	490	686	980	1000	1400	1800
SIZES								
Internal width (mm)	500	700	700	700	1000	1000	1000	1000
Internal depth (mm)	450	700	700	700	700	1000	1000	1000
Internal height (mm)	500	700	1000	1400	1400	1000	1400	1800
External width* (mm)	750	941	941	1164	1464	1464	1464	1464
External depth* (mm)	916	1160	1143	1221	1240	1545	1538	1535
External height* (mm)	1165	1360	1692	2068	2060	1650	2089	2506
External height with sub-frame option*	1875	1850	2050	2274	2207	2020	-	-
Floor height with sub-frame option*	850	700	600	400	400	600	-	-
Weight, empty (kg)	136	198	218	332	410	470	638	736
Number of door(s)	1	1	1	1	1	1	1	1
PERFORMANCES								
Temperature range (°C)	Ambient + 20°C up to 200°C (300°C optional)							
Temperature fluctuation (+/- °C)	< 0.2							
Fan air flow (m³/h)	450	600	600	1300	1800	1800	2500	2500
Ø air inlet and hot air outlet (mm)	63	80	80	80	80	80	100	100
ELECTRICAL DATA								
Heating power (W)	3000	6000	6000	9000	12000	12000	15000	18000
Total installed power (VA)	3428	6816	6816	9954	12954	12954	16402	19402
Power	230V 1phase +PE, 50Hz			400V, 3 phases + PE, 50Hz				
Amperage connection (A)	16/20	20	20	20	25	25	25	32
SHELVES								
Maximum number	8	11	17	24	24	17	24	30
Maximum load per shelf / in the oven (kg)	30 / 100	30 / 180	30 / 180	30 / 200	30 / 240	30 / 240	30 / 280	30 / 320
Shelves sizes (LxP) (mm)	470x420	670x670	670x670	670x670	970x670	970x970	970x970	970x970

* some options may change the sizes of the oven



Order a few click...

www.france-etuves-store.com

Web, mobile, tablet, order easily and receive your products quickly !



www.france-etuves-store.com



**FRANCE
ETUVES**
Ovens Designer & Manufacturer

65/67 rue Auguste Meunier
77500 CHELLES, FRANCE

T : +33 1 64 21 30 60

F : +33 1 64 21 30 86