

# DS-FS20E

[desmonscientific.com/](http://desmonscientific.com/)



## BLOOD BANK CONTROLLER FEATURES

End user interface	Display LED
Resolution (°C)	0,1
Maximum Number of Probes	3
Internal Led light	yes
Acoustic alarm	yes
Hot gas advanced defrost	yes

## ALARMS AND FAILURES (ACOUSTIC AND VISUAL)

HACCP function	yes
"Power failure" (back up battery) Alarm	yes
"High / low temperature" Alarm	yes
"Open door" Alarm	yes

"Sensor fault"Alarm	yes
Clogged condenser Alarm	yes
Temperature datalogger with USB port	yes
CONNECTIONS	
RS 485 interface	optional
Porta Ethernet (LAN)	optional
SAFETY	
Switch on/off protected by password	yes
Dry Contact for alarms remoting	yes
Freezing and overheating safety device	yes
OPTIONALS	
Rechargeable back-up batteries	optional
STRUCTURE	
Exterior dimensions WxDxH (mm)	600x600x1560
Capacity (L)	200
N of blood bags (450ml)	128
Insulation (mm)	60
Temperature range (°C)	+4°C
Max. ambient temperature (°C)	43
Type of cooling unit	Ventilated
Power supply (V)	220V/240V
Frequency (Hz)	50
Power consumption (W)	245
Weight (KG)	94
Shipping weight (KG)	105
Shipping dimensions WxDxH (mm)	680x680x1790
No. of compressors.	1
Doors	1 glass door
Automatic (smart) defrost and evaporation	yes

Castors	yes
Chart recorder	yes
Drawers (pcs)	4 s/steel drawers
Lock	yes
Interior material	s/steel AISI304
Exterior material	White powder coated steel
Gas	R404a

Price: € 0,00