

DS-FS20V

desmonscientific.com/



FEATURES OF LAB PRO ELECTRONIC CONTROLLER

End user interface	Display LED
Resolution (°C)	0,1
Maximum Number of Probes	3
Internal Led Light	yes
Acoustic alarm	yes
Hot gas advanced defrost	yes

ALARMS AND FAILURES (ACOUSTIC AND VISUAL)

HACCP function	yes
"Power failure" (back up battery) Alarm	yes

"High / low temperature" Alarm	yes
"Open door"Alarm	yes
"Sensor fault"Alarm	yes
Clogged condenser Alarm	yes
Temperature datalogger with USB port	yes
CONNECTIONS	
RS 485 interface	optional
Porta Ethernet (LAN)	optional
SAFETY	
Dry Contact for alarms remoting	yes
Freezing and overheating safety device	yes
OPTIONALS	
Rechargeable back-up batteries	optional
SMS alerts	optional
STRUCTURE	
Exterior dimensions WxDxH (mm)	600x600x1560
Net Capacity (L)	200
Insulation (mm)	60
Temperature range (°C)	+2° +12°C, Factory setting+4°
Max. ambient temperature (°C)	43
Refrigeration type	Ventilated
Power supply (V)	220V/240V
Frequency (Hz)	50
Power consumption (W)	245
Weight (KG)	91

Shipping weight (KG)	102
Shipping dimensions WxDxH (mm)	680x680x1790
No. of compressors.	1
Doors	1 glass door
Defrost	Automatic
Wheels	standard
Chart recorder	optional
Racks (pcs)	3
Lock	yes
Interior material	s/steel AISI304
Exterior material	hot-dip galvanised steel, anti-corrosion treated and white PVC film coated
Refrigerant	R404a

Price: € 0,00