

# DS-GB14

[desmonscientific.com/](http://desmonscientific.com/)



## STANDARD CONTROLLER FEATURES

End user interface	Display LED
Resolution (°C)	0,1
Maximum Number of Probes	3
Internal Led light	optional
Acoustic alarm	yes
Hot gas advanced defrost	yes

## ALARMS AND FAILURES (ACOUSTIC AND VISUAL)

HACCP function	yes
"Power failure" Alarm	yes
"High / low temperature" Alarm	yes
"Open door" Alarm	yes
"Sensor fault" Alarm	yes

Clogged condenser Alarm	yes
Alarm recording (data logger of events - alarms)	yes
CONNECTIONS	
RS 485 interface (not available if temperature data logger with USB port is installed)	optional
SAFETY	
Dry Contact for alarms remoting	yes
Freezing and overheating safety device	yes
OPTIONALS	
Rechargeable back-up batteries	optional
Temperature datalogger with USB port	optional

STRUCTURE	
Exterior dimensions WxDxH (mm)	1440x800x2120
Capacity (L)	1400
Interior dimensions WxDxH (mm)	1320x665x1520
Insulation (mm)	60
Temperature range (°C)	-10°-25°
Max. ambient temperature (°C)	43
Type of cooling unit	Monoblock
Power supply (V)	220V/240V
Frequency (Hz)	50
Power consumption (W)	780
Weight (KG)	185
Shipping weight (KG)	205
Shipping dimensions WxDxH (mm)	1500x860x2280
No. of compressors.	1
Doors	2
Automatic (smart) defrost and evaporation	yes
Castors	optional
Chart recorder	optional
Shelves (pcs)	6

---

Lock	yes
Interior material	s/steel AISI304
Exterior material	s/steel AISI304
Gas	R404a

---

Price: € 0,00